

- Technical Data Sheet: LPI 25mm x 3mm Copper Tape (CT253)
 - Copper Purity: 99.993%
 - European designed extrusion technology
 - Mill Certificate available upon request



LPI® 25mm x 3mm Copper Tape (CT253)

• Product Description

LPI's 25mm x 3mm soft drawn copper tape is manufactured using the latest European developed extrusion technologies. The copper tape is supplied with LPI's trademark and web address embossed on the tape for customised identification.

LPI's CT253 is a high quality tape which provides our customers with a guaranteed copper purity of 99.993%.

The CT253 is suitable for installation in many earthing applications and for use as a conventional downconductor as part of a lightning protection system.



• Technical Data

Ordering Code:	CT253
Copper Purity:	99.993%
Width:	24.87mm
Thickness:	2.83mm
Electrical Conductivity:	100.5% I.A.C.S
Embossing:	" LPI® " " www.lpi.com.au "
Packaged:	Supplied in 100 metre pancakes. Contact LPI for variable lengths.



- **"LPI Endorsed Product"** – The symbol of assurance of quality and performance.
- LPI has a policy of continuing product development. Therefore, the above specifications are subject to change without notice.

LPI® - Innovative Lightning and Surge Protection Solutions



Direct Strike Protection



Surge & Transient Protection for Power, Data, Communications and RF lines



Grounding Products & Solutions

Lightning Protection International Pty Ltd. A.C.N: 099 190 897

Page: 1 of 1

Complex 1, 16 Mertonvale Circuit, Kingston Tasmania 7050, Australia

Phone: +61 3 62271955

Fax: +61 3 62291900

Email: info@lpi.com.au

Web: www.lpi.com.au

Commercial in Confidence

Copyright ©2004 LPI