
- **Technical Data Sheet: EARTH PITS**

- Secure protection for all earthing terminations
 - Lightweight and heavy duty earth pits
 - Suitable for pathing and hot tar applications
-



LPI® EARTH PITS

- **Product Description**

All earthing terminations are required to be safely and securely located so as to maintain the integrity of all earthing connections.

Recommended maintenance and inspection of earthing terminations is essential in order to ensure the safety of personnel and equipment when earth fault currents, and high current levels enter the earthing system via lightning protection installations.

The LPI range of earth pits provide variable options for the safe and access friendly installation of your earthing terminations.

- **Technical Data**

Ordering Code: EPIT-L
Dimensions: 235mm Top, 335mm Bottom, 255mm Deep
Construction: Plastic
Weight: 1.4Kg
Colour: Green
Withstand: 1 Tonne
Warranty: 5 Years



Ordering Code: EPIT-H
Dimensions: 435mm Top, 300mm Bottom, 200mm Deep
Construction: Plastic
Weight: 3Kg
Colour: Green
Withstand: 5 Tonnes
Warranty: 5 Years



Ordering Code: EPIT-C
Dimensions: 330mm Top, 330mm Bottom, 300mm Deep
Construction: Glass fibre reinforced concrete
Weight: 12Kg
Colour: Grey
Withstand: Suits all load applications from pedestrian to highway traffic
Warranty: 5 Years.



- **"LPI Endorsed Product"** – The symbol of assurance of quality and performance.
- LPI has a policy of continuing product development. Therefore, the above specifications are subject to change without notice.

LPI® - Innovative Lightning and Surge Protection Solutions



Direct Strike Protection



Surge & Transient Protection for Power, Data, Communications and RF lines



Grounding Products & Solutions

Lightning Protection International Pty Ltd. A.C.N: 099 190 897

Page: 1 of 1

Complex 1, 16 Mertonvale Circuit, Kingston, Tasmania 7050, Australia

Phone: +61 3 6227 1944

Fax: +61 3 6229 1900

Email: info@lpi.com.au

Web: www.lpi.com.au

Commercial in Confidence

Copyright ©2004